

Reynolds Boughton AirField Crash Tender Chassis 4x4, 6x6



TRUCK CHASSIS



TRUCK CHASSIS



TRUCK CHASSIS

AIRFIELD SAFETY 1982

REYNOLDS BOUGHTON AIRFIELD CRASH TENDER CHASSIS

MODEL	APOLLO	PEGASUS	PERSEUS	PROTEUS	ALPHA	BETA	GAMMA	DELTA	EPSILON	ZETA	ETA	THETA	IOTA	KAPPA	LAMDA	MU	NU	Xi	Omicron	Psi	Omega
Overall Length	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	
Overall Width	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4	4.6	4.8	5.0	5.2	5.4	5.6	5.8	
Wheelbase	1.5	1.8	2.1	2.4	2.7	3.0	3.3	3.6	3.9	4.2	4.5	4.8	5.1	5.4	5.7	6.0	6.3	6.6	6.9	7.2	
Ground Clearance	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	
Max. Speed	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	
Max. Towing Capacity	1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3200	3400	3600	3800	4000	4200	4400	4600	4800	
Max. Gross Weight	1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3200	3400	3600	3800	4000	4200	4400	4600	4800	
Max. Payload	1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3200	3400	3600	3800	4000	4200	4400	4600	4800	
Max. Fuel Capacity	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Water Capacity	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Air Capacity	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Foam Capacity	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Nozzle Pressure	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Diameter	1.5	1.8	2.1	2.4	2.7	3.0	3.3	3.6	3.9	4.2	4.5	4.8	5.1	5.4	5.7	6.0	6.3	6.6	6.9	7.2	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Length	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	460	480	
Max. Hose Weight	100	120	140	160	180	200	220	240	260	280	300	320	340	360	380	400	420	440	46		

REYNOLDS BOUGHTON CHASSIS

ADVANCED FIRE FIGHTING VEHICLES



Reynolds Boughton "Phoenix"
4 x 4 chassis G.V.W. 25-26 ton



Reynolds Boughton "Pegasus"
4 x 4 chassis G.V.W. 7 tons

Page 20

REYNOLDS BOUGHTON CHASSIS

ADVANCED FIRE FIGHTING VEHICLES

IN USE ON THE WORLD'S MAJOR INTERNATIONAL
CIVIL AIRPORTS AND MILITARY AIRFIELDS

Reynolds Boughton "Aquarius"
6 x 6 chassis G.V.W. 22 ton



Reynolds Boughton "Griffin"
6 x 6 chassis G.V.W. 38 ton



Page 19